Reasoning-enhanced Query Understanding through Decomposition and Interpretation

Yunfei Zhong* Institute of Computing Technology, Chinese Academy of Sciences Beijing, China zhongyunfei25@mails.ucas.ac.cn

> Lixin Su Baidu Inc. Beijing, China sulixinict@gmail.com

Jun Yang*
Institute of Computing Technology,
Chinese Academy of Sciences
Beijing, China
yangjun24s@ict.ac.cn

Maarten de Rijke University of Amsterdam Amsterdam, The Netherlands m.derijke@uva.nl

Xueqi Cheng
Institute of Computing Technology,
Chinese Academy of Sciences
Beijing, China
cxq@ict.ac.cn

Yixing Fan[†]
Institute of Computing Technology,
Chinese Academy of Sciences
Beijing, China
fanyixing@ict.ac.cn

Ruqing Zhang
Institute of Computing Technology,
Chinese Academy of Sciences
Beijing, China
zhangruqing@ict.ac.cn

Abstract

Accurate inference of user intent is crucial for enhancing document retrieval in modern search engines. While large language models (LLMs) have made significant strides in this area, their effectiveness has predominantly been assessed with short, keyword-based queries. As AI-driven search evolves, long-form queries with intricate intents are becoming more prevalent, yet they remain underexplored in the context of LLM-based query understanding (QU). To bridge this gap, we introduce **ReDI**: a **Reasoning**-enhanced approach for query understanding through **Decomposition** and **Interpretation**. ReDI leverages the reasoning and comprehension capabilities of LLMs in a three-stage pipeline: (i) it breaks down complex queries into targeted sub-queries to accurately capture user intent; (ii) it enriches each sub-query with detailed semantic interpretations to improve the query-document matching; and (iii) it independently retrieves documents for each sub-query and employs a fusion strategy to aggregate the results for the final ranking. We compiled a large-scale dataset of real-world complex queries from a major search engine and distilled the query understanding capabilities of teacher models into smaller models for practical application. Experiments on BRIGHT and BEIR demonstrate that ReDI consistently surpasses strong baselines in both sparse and dense retrieval paradigms, affirming its effectiveness. We release our code at https://anonymous.4open.science/r/ReDI-6FC7/.

Keywords

Query understanding, Knowledge distillation, Large language model

1 Introduction

Query understanding (QU) aims to infer the user's intent behind a query to improve the retrieval of relevant documents. It has become a fundamental component of modern search engines [6], as it is both effective and straightforward to integrate into existing search systems. However, due to the inherent flexibility of language and the implicit nature of user intent, accurately inferring the user's true information needs from their query is a significant challenge.

To address this challenge, prior work has developed QU methods that incorporate diverse sources of information, such as external knowledge and pseudo-relevance feedback (PRF). On the one hand, knowledge-based methods [2, 10, 19, 34] enrich query representations with structured resources like WordNet, Wikipedia, and user logs. On the other hand, PRF-based methods [3, 20, 29, 30] assume that the top-k retrieved documents are relevant to the initial query, allowing them to serve as a source of contextual information for query enrichment. Although both strategies often yield noticeable gains in retrieval performance, they tend to depend either on fixed heuristic rules or on the quality of retrieved pseudo-documents. This dependence constrains their capacity to uncover deeper, latent user intent and often results in query drift or misinterpretation, especially when handling ambiguous or concise queries [4].

In recent years, large language model (LLM)-based query understanding methods have proven effective by leveraging the extensive linguistic and world knowledge learned during pre-training [13, 36]. These approaches prompt an LLM to infer user intent and optimize it to capture richer semantic representations aligned with target documents [5, 26, 41]. However, most prior studies have evaluated their effectiveness within traditional retrieval settings, where users issue keyword-based queries to locate relevant documents for a specific task, a process we term **information-locating retrieval**.

With the rapid advancement of LLM reasoning and generation capabilities, AI-driven search systems such as OpenAI [27],

^{*}Co-first authors. Work done during internship at Baidu Inc.

[†]Corresponding author.

DeepSeek [16], and Gemini [15] have enabled more complex forms of information seeking. In these settings, user queries often involve multiple entities, extended temporal scopes, and diverse knowledge domains, demanding sophisticated reasoning. For example, a query like "How has the relationship between scientific development and capital evolved from the Industrial Revolution to the present?" requires the integration of dispersed historical evidence and conceptual synthesis. We refer to this paradigm as **reasoning-intensive retrieval** [32], which poses substantial challenges for existing systems that struggle to accurately interpret, decompose, and satisfy such multifaceted information needs.

Recent studies have sought to exploit the reasoning capabilities of LLMs to enhance retrieval performance on complex tasks, e.g., ReasonIR [31], ReasonRank [23], and DIVER [24]. While these approaches yield strong performance, they often come with substantial computational costs. A natural way to handle complexity is through divide-and-conquer strategies, however, prior work suggests that an information-rich long query often outperforms decomposed ones [31]. This raises a key question that we investigate in this paper: when addressing complex queries, is query decomposition inherently ineffective, or is its application the real issue?

Proposed query understanding method. To address this, we propose ReDI, a reasoning-enhanced query understanding model that combines both decomposition and interpretation. Specifically, we design a three-stage LLM-based pipeline: (i) Decompose a complex query into sub-queries to cover diverse user intents. (ii) Augment each sub-query with semantic interpretation to improve alignment between intent and document content. (iii) Fuse the retrieval results with a dedicated aggregation strategy to produce the final ranking. Moreover, we introduce tailored query prompts for both sparse and dense retrieval, enhancing ReDI's adaptability across different settings. By explicitly decomposing complex queries and interpreting each sub-intent, ReDI achieves broader coverage and more precise retrieval, delivering strong performance even with simple models such as BM25 and SBERT.

A new dataset for query understanding. To support development, we have curated a large-scale, comprehensive dataset of complex queries, meticulously filtered from both general and AI-driven search logs of a major commercial search engine. Using DeepSeek-R1, we generate high-quality intent annotations, which serve as supervision to distill a compact student model tailored for real-world production environments. This approach enables efficient, scalable, and privacy-preserving query understanding without compromising performance.

Experiments on public retrieval benchmarks, including BEIR [33] and BRIGHT [32], demonstrate that ReDI consistently outperforms strong QU baselines for both sparse and dense retrieval. Moreover, our distilled model matches or even surpasses the performance of its teacher in generating high-quality, intent-aware queries, further validating the practicality and scalability of our model.

Main contributions. We have three main contributions:

 We show that decomposition remains an effective approach for handling complex queries, however, it requires complementary interpretations to boost retrieval performance. To this end, we

- propose the ReDI model, which delivers strong performance using lightweight retrieval methods.
- We construct and release a large-scale, real-world complex query dataset derived from the logs of a major commercial search engine, and distill the query understanding capabilities of DeepSeek-R1 into a lightweight, production-ready model.
- We conduct extensive experiments on BEIR and BRIGHT, including effectiveness comparison, ablation studies, strategy optimizations, and transferability evaluations. Results show that ReDI outperforms strong baselines and demonstrate robust generalization across datasets and tasks.

2 Related Work


2.1 Traditional query understanding


Traditional QU methods have aimed to mitigate the lexical mismatch problem by enriching queries with additional relevant terms such as synonyms, terms on the same topic, and words with the same root. These approaches typically fall into two main categories based on the sources: external knowledge-based and PRF methods. Firstly, external knowledge-based approaches expand the original query by incorporating semantically related terms from resources like WordNet or Wikipedia [2, 12, 34]. For example, Voorhees [34] uses WordNet to expand semantically similar terms, and Gabrilovich and Markovitch [12] employs explicit semantic analysis to embed queries into a Wikipedia-derived concept space. Some researchers also employ anchor text [10, 19] and user logs [9, 37] to extract related terms. Secondly, PRF approaches use topranked pseudo-relevant documents from initial retrieval to derive expansion terms [11, 20, 29]. For example, Carpineto et al. [3] employs Kullback-Leibler divergence (KLD) to assess the differences in term distribution between pseudo-relevant documents and the complete document set.

Despite their effectiveness in specific scenarios, these methods have limitations such as reliance on predefined static semantic resources or susceptibility to semantic drift resulting from the quality of initial retrieval sets [8, 25].

2.2 LLM-based query understanding

Recent advancements in LLMs have paved the way for novel QU approaches that exploit the generative capabilities of these models [13, 26, 36]. Methods such as HyDE [13] and Query2Doc [36] use LLMs to generate hypothetical documents or pseudo-answers, significantly enhancing the semantic richness of queries. RRR [26] uses LLMs to train a small rewriting model via reinforcement learning, while RAG-STAR [17] integrates retrieved information to guide a tree-based decomposition process. RQ-RAG [5] enhances models by equipping them with capabilities for explicit rewriting, decomposition, and disambiguation. STEP-BACK [41] performs abstractions to derive high-level concepts and first principles from the original query. Lei et al. [21] iteratively refines expansions using retrieval feedback from the corpus. On short queries, LLM-based QU methods have shown improved alignment with relevant documents compared to traditional approaches.








Figure 1: The three-step ReDI workflow.

2.3 Reasoning-intensive retrieval

Complex queries, which often involve multiple entities, broader temporal scopes, and diverse knowledge domains, pose significant challenges to existing QU methods. The recently introduced BRIGHT benchmark [32] offers a structured framework for evaluating QU techniques on such queries, which require intensive reasoning to retrieve relevant information.

To tackle these challenges, recent studies have explored leveraging the reasoning capabilities of LLMs to enhance retrieval effectiveness, broadly falling into two categories. The first focuses on **reasoning-augmented ranking**, where ranking models are built upon reasoning-oriented LLMs [23, 24, 31]. For example, ReasonIR [31] constructed a reasoning-intensive retrieval dataset to train a Llama3.1-based retriever, while ReasonRank [23] developed a reasoning-enriched dataset to train Qwen2.5 as a listwise reranker. The second category leverages LLMs for **reasoning-based query understanding**, enhancing query representations through generative augmentation [21, 24, 28]. For example, Long et al. [24] designs a feedback-driven query expansion process inspired by [21]. These approaches iteratively refine the query based on the retrieved context.

Our work aligns with the latter line of research but takes a distinct perspective: rather than drilling down into the query's intent, we focus on *decomposing* the query to uncover and address its multi-dimensional information needs.

3 Methodology

We propose **ReDI**, a structured query understanding model that employs LLMs to systematically process complex queries through three distinct stages: (i) **intent reasoning and decomposition**, where the query is analyzed and broken down into focused subqueries; (ii) **sub-query interpretation generation**, where each sub-query is enriched with alternative phrasings and additional contextual information; and (iii) **retrieval results fusion**, where each enriched sub-query is independently retrieved, and their results are combined through a fusion strategy into a final ranking. Figure 1 illustrates the overall workflow of ReDI. Below, we detail each component.

3.1 Intent reasoning and query decomposition

Complex queries frequently encompass multiple implicit sub-intents and require multi-hop information retrieval (IR) from various sources[39]. Treating these queries as a single retrieval unit often leads

to incomplete results[1]. To mitigate this, we first explicitly identify the underlying intent of the original query and decompose it into targeted, independently retrievable sub-queries.

Specifically, given a query $q_i \in Q$, we first prompt an LLM to uncover what the user fundamentally seeks. By **reasoning** about the core intent, the model identifies whether the query is composed of multiple sub-intents or logical components. We then guide the model to dynamically **decompose** q_i into a set of clear, concise, and independent sub-queries $S_i = \{s_1, s_2, ..., s_m\}$, each corresponding to a specific aspect of the overall information need. This explicit decomposition ensures thorough coverage of the multi-hop or multi-faceted nature inherent in complex queries, enabling targeted retrieval of documents relevant to each distinct facet.

3.2 Sub-query interpretation generation

The decomposed sub-queries lack the descriptive depth needed for the retriever to effectively identify relevant documents. Here, we argue that the detailed explanations of each sub-query are essential for improving retrieval performance. To this end, we propose leveraging LLM to generate context-aware **interpretations** that enrich each sub-query. These interpretations incorporate alternative phrasings, domain-specific terminology, and broader contextual cues. Furthermore, we have designed distinct interpretation strategies, each specifically tailored to different retrieval methods.

For sparse retrieval (e.g., BM25), which relies on exact term overlap, interpretations emphasize lexical diversity, introducing synonyms, morphological variants, and related terminology to improve recall. For example, the sub-query "effects of a low-infrared light on insect behavior" may be expanded with terms like "LED lights", "insects attracted to light", or "heat vs light attraction" to cover varied expressions of the same concept.

For dense retrieval, which matches queries and documents based on semantic similarity, interpretations take the form of paraphrases or elaborations that place the sub-query in a richer conceptual frame. In the same example, this might include phrases like "insect behavioral response to light sources" or "evolutionary drivers of light attraction in insects". Such semantically grounded expansions help the retriever to embed the query more effectively and retrieve relevant content even in the absence of lexical overlap.

Beyond lexical and semantic enrichment, we also prompt the LLM to generate a brief reasoning interpretation for each sub-query, capturing the underlying rationale or implicit assumptions behind the information need. These interpretations provide an additional layer of context, guiding the retriever toward passages that align

not only with the surface form of the query but also with its deeper intent. This structured, context-aware interpretation strategy enhances the likelihood of retrieving relevant evidence across both sparse and dense settings.

3.3 Retrieval result fusion

Previous QU approaches, such as the reasoning-expansion introduced by BRIGHT [32], typically use the LLM-generated reasoning as a single long-form expanded query. However, such lengthy queries easily introduce excessive noise, dilute key term importance, and confuse the retrieval model [35]. To mitigate these issues, we decompose each complex query into multiple sub-queries and enrich them with detailed explanations. This allows each sub-query to focus on a specific aspect of the original query, enabling more precise retrieval with lightweight retrievers.

Sparse retrieval. In sparse retrieval, each retrieval unit is independently scored using the BM25 function. Given a sub-query s_i with its interpretation e_i and a candidate document d, we construct the query representation by simple concatenation:

$$\hat{s_i} = s_i \oplus e_i. \tag{1}$$

The trade-off between a query and its expansion has been investigated in prior studies [7, 40], and we leave its exploration to future work.

$$\operatorname{Sparse}(\hat{s_i}, d) = \sum_{t \in \hat{s_i} \cap d} \operatorname{IDF}(t) \cdot \frac{f_d(t) \cdot (k_1 + 1)}{f_d(t) + k_1 \cdot \left(1 - b + b \cdot \frac{|d|}{\operatorname{avgdl}}\right)} \cdot \frac{f_{\hat{s_i}(t)} \cdot (k_3 + 1)}{f_{\hat{s_i}(t)} + k_3},$$
 (2)

where the \oplus operator denotes the concatenation of two texts, $f_d(t)$ and $f_{\hat{s}_i}(t)$ denote the frequency of term t in document d and \hat{s}_i , respectively; |d| is the document length, avgdl is the average document length in the corpus, and IDF(t) is the inverse document frequency. The hyperparameters k_1 , b, and k_3 control document term frequency scaling, length normalization, and query term frequency saturation, respectively.

In particular, we emphasize the role of k_3 , which controls the impact of query-side term frequency. A smaller k_3 amplifies the effect of repeated key terms, making the retriever more sensitive to core lexical cues, whereas a larger k_3 reduces saturation, favoring broader coverage across terms. Although many modern BM25 implementations omit this parameter, prior work has noted its potential impact, especially for long and reasoning-intensive queries [22]. Recent analyses further highlight how different BM25 implementations—particularly whether query-side term frequency is saturated or not—can lead to notable effectiveness differences on BRIGHT [14]. We provide a detailed study of the impact of k_3 in the hyperparameter sensitivity experiments reported in Section 6.2.

Dense retrieval. For dense retrieval, we follow the prior bi-encoder model DPR[18] to encode each sub-query and its corresponding interpretation using a shared dense encoder $f(\cdot)$. A fused query embedding is constructed as a weighted combination of the two, and its similarity to a document embedding is computed via inner product:

Dense
$$(s_i, e_i, d) = \langle \lambda \cdot f(s_i) + (1 - \lambda) \cdot f(e_i), f(d) \rangle,$$
 (3)



Figure 2: The Coin selection workflow.

where s_i and e_i are the i-th sub-query and its interpretation, respectively. The scalar $\lambda \in [0,1]$ adjusts the relative contribution of the original sub-query semantics and the enriched interpretation. This formulation enables the retrieval model to attend both to the core information need and its contextual elaboration.

Fusion strategy. Once all retrieval units have been independently scored, we aggregate the results to compute the final document score. Let $S = \{s_1, s_2, \ldots, s_m\}$ and $E = \{e_1, e_2, \ldots, e_m\}$ denote the set of m sub-queries and corresponding interpretations for query q. The final relevance score for a document d is computed by summing its scores across all units:

$$score(q, d) = \sum_{s_i \in S, e_i \in E} Retrieval(s_i, e_i, d),$$
(4)

where Retrieval(s_i , e_i , d) corresponds to either Sparse(s_i , e_i , d) defined in Eq. 2 or Dense(s_i , e_i , d) defined in Eq. 3. This additive fusion approach prioritizes documents that are relevant to multiple retrieval units, thereby capturing the compositional structure of complex queries and aligning more faithfully with the user's complete information need. We also studied several alternative fusion strategies, which are discussed in Appendix A.1.

4 Dataset Collection & Model Training

To train ReDI for accurate understanding, decomposition, and interpretation of complex queries, we construct a dataset of real user queries that naturally embody multifaceted intents. Based on this dataset, we conduct knowledge distillation to develop compact models with enhanced complex query understanding capabilities.

4.1 Creation of the Coin dataset

To address this gap, we propose the Complex Open-domain INtent (COIN) dataset, which targets complex queries from a major search engine. Drawing from real search logs, the COIN dataset reflects genuine user needs that are open-domain (spanning diverse topics) and complex (involving multiple reasoning steps or aspects). We construct the COIN dataset from two sources: about 100k queries from general search, which emphasize challenging single-turn queries for information-locating retrieval, and about 10k queries from AI search, which emphasize multi-turn queries for reasoning-intensive retrieval. We illustrate their differences in Appendix A.1.

As shown in Figure 2, the construction of Coin proceeds through four stages. We begin with source-specific filtering, where general search queries are pruned by engagement signals (reducing ~100k to ~41k) and AI search queries are retained only if they exhibit substantive multi-turn context (reducing ~10k to ~10k). Next, a quality validation stage ensures adequate length, linguistic clarity, and legitimacy; DeepSeek-R1 is used to verify fluency and remove trivial, incomplete, or sensitive queries, leaving ~16k and ~6k queries. This is followed by **complexity refinement**, where general search queries solvable by top-4 retrievals are discarded (~4k remain), while AI search queries are filtered by a complex intent classifier to preserve those requiring multi-dimensional reasoning, comparison, or synthesis (~2.8k remain). Finally, a curation stage merges and de-duplicates both sources, with manual review ensuring diversity and representativeness, yielding 2,056 general search queries and 1,347 AI search queries. In total, the Coin dataset contains 3,403 unique complex queries.

4.2 Efficient model fine-tuning

To enable structured intent understanding, we fine-tune models on the Coin dataset for three sub-tasks: query decomposition, sparseoriented interpretation, and dense-oriented interpretation. As the dataset lacks ground-truth labels, we employ DeepSeek-R1 to generate high-quality annotations and explore two paradigms:

- 4.2.1 Two-stage Fine-tuning. We train a decomposition model and two interpretation models separately:
- **Decomposition.** Given a raw query q, the model generates a set of sub-queries $\{s_i, \ldots, s_m\}$, each targeting one facet of the information need.
- Interpretation. For each s_i, two models produce corresponding interpretations e_i: (a) Sparse-oriented: focus on lexical richness (synonyms, derivations, domain-specific terms). (b) Dense-oriented: emphasize semantic clarity and paraphrasing.

The objective minimizes sequence generation loss:

$$\mathcal{L}_{\text{two-stage}} = \mathbb{E}q \sim Q \left[\sum_{i=1}^{N} \left(\log P(s_i \mid q) + \log P(e_i \mid s_i) \right) \right]. \quad (5)$$

4.2.2 *Joint Fine-tuning.* Alternatively, we jointly fine-tune a single model to perform decomposition and interpretation generation in one pass. Given a query q, the model outputs interleaved subqueries and their corresponding interpretations in parallel:

$$q \to (s_1, e_1), \dots, (s_m, e_m). \tag{6}$$

We optimize a joint loss:

$$\mathcal{L}_{\text{joint}} = \alpha \mathcal{L}_{\text{decomp}} + (1 - \alpha) \mathcal{L}_{\text{interp}}, \tag{7}$$

with α controls the balance between the learning of decomposition and contextual relevance.

All fine-tuned models are referred to as **ReDI**. As shown in Section 6, both variants achieve strong performance on BRIGHT, rivaling or surpassing larger baselines.

5 Experiment

5.1 Experimental setup

- 5.1.1 Datasets. We evaluate our method on two prominent retrieval benchmarks: **BRIGHT** and **BEIR**, covering a wide range of real-world query scenarios. BRIGHT[32] is a reasoning-intensive benchmark with 1,384 real-world queries across *StackExchange*, *Coding*, and *Theorem-based*, including a long-document subset of StackExchange tasks where queries are matched against full-length web pages with higher token counts and noise. BEIR[33] is a heterogeneous IR benchmark of 18 datasets; following prior work Rank1 [38], we evaluate on a subset of 9 datasets with fewer than 2,000 queries: (*ArguAna*, *Climate-FEVER*, *DBPedia*, *FiQA-2018*, *NF-Corpus*, *SciDocs*, *SciFact*, *Webis-Touche2020*, *TREC-COVID*).
- 5.1.2 Metrics. Following BRIGHT and Rank1, we adopt nDCG@10 as the primary evaluation metric. Specifically, for the long-document subset of BRIGHT, we follow BRIGHT and report Recall@1.
- 5.1.3 Baselines. We use the reasoning expansion variants released in the official BRIGHT dataset repository¹, generated by Claude-3-opus and GPT-4, as our baselines. Moreover, we generate reasoning-based expansions with DeepSeek-R1 using the same prompt as in BRIGHT. In addition, we incorporate several recently proposed state-of-the-art methods, i.e., TongSearch-QR [28], ThinkQE [21], and DIVER-QExpand [24], as baselines for comparison.
- 5.1.4 Training Details. We fine-tune Qwen3-8B 2 on the CoIN dataset described in Section 4.1, using a learning rate of 1×10^{-4} with 10 % linear warm-up and cosine decay. All experiments are conducted on a single NVIDIA A100 GPU.
- 5.1.5 Evaluation Procedure. We evaluate QU methods under both sparse and dense paradigms, using two representative lightweight retrievers. For Sparse Retrieval, we use Gensim's LuceneBM25Model³ with Pyserini⁴ analyzers. Baselines use reasoning-expanded queries with the BRIGHT BM25 setting (k_1 =0.9, b=0.4). ReDI modifies this setup by adjusting k_3 , setting it to 0.4 for short documents and 5 for long ones. For Dense Retrieval, we use SBERT⁵, a relatively lightweight bi-encoder model that encodes queries and documents into 768-dimensional embeddings. ReDI embeds each sub-query and interpretation, fuses them by weighted average (λ = 0.5 for BRIGHT, 0.4 for long documents). For model learning, we set α = 0.5 to balance the contribution of both decomposition and interpretation.

All experiments are zero-shot: ReDI is only trained on COIN without exposure to BRIGHT or BEIR, ensuring the fair evaluation.

5.2 Main results

Table 1 reports the retrieval performance (nDCG@10) of different QU methods on BRIGHT. Key observations include:

• Sparse retrieval. Our ReDI consistently improves the performance on BM25, achieving the highest average nDCG@10 of 30.8%. Compared to single long-form expansion methods (Claude-3-opus, GPT-4, DeepSeek-R1), ReDI's structured decomposition

 $^{^{1}} https://hugging face.co/datasets/xlangai/BRIGHT \\$

²https://huggingface.co/Qwen/Qwen3-8B

https://pypi.org/project/gensim/
 https://pypi.org/project/pyserini/

 $^{^{5}} https://hugging face.co/sentence-transformers/all-mpnet-base-v2$

Table 1: nDCG@10 on BRIGHT Benchmark. Best scores are in bold, second-best are underlined. *Results from SU et al. [32].
†Results from Long et al. [24]. Avg.All and Avg.SE denote average performance across all and StackExchange tasks, respectively.

OU Model	Params	Avg.All	Avø SE			Stack	Exch	ange			Cod	ding	Th	eorem-b	OQ. TheoT. 10.4 4.9 19.0 18.1 19.2 20.8 26.3 23.4 26.1 22.0 27.0 21.4 23.4 20.4 11.5 30.0					
20 1/10401	1 111 11111		11, 8,52	Bio.	Earth.	Econ.	Psy.	Rob.	Stack.	Sus.	Leet.	Pony	AoPS	TheoQ.	TheoT.					
				U	sing BN	125 Ret	trievei	•												
-	-	14.5	17.2	18.9	27.2	14.9	12.5	13.6	18.4	15.0	24.4	7.9	6.2	10.4	4.9					
Claude-3-opus*	-	26.8	34.4	54.2	52.1	23.5	38.4	22.5	24.1	26.0	20.0	19.6	4.1	19.0	18.1					
GPT4*	-	27.0	34.8	53.6	54.1	24.3	38.7	18.9	27.7	26.3	19.3	17.6	3.9	19.2	20.8					
DeepSeek-R1	671B	29.2	<u>37.0</u>	57.2	58.1	24.0	38.1	22.1	<u>29.6</u>	<u>29.6</u>	22.2	12.4	6.8	26.3	<u>23.4</u>					
TongSearch-QR [†]	7B	27.9	32.9	57.9	50.9	21.9	37.0	21.3	27.0	25.6	23.6	14.4	7.0	26.1	22.0					
ThinkQE [†]	14B	30.0	33.6	55.9	52.3	26.5	39.0	22.9	27.9	30.9	25.2	20.9	10.3	27.0	21.4					
DIVER-QExpand [†]	14B	29.5	37.0	56.7	54.5	25.9	43.9	23.2	27.0	28.8	25.6	16.6	8.7	23.4	20.4					
ReDI(ours)	8B	30.8	38.3	49.0	53.5	28.7	<u>43.4</u>	27.5	36.3	29.4	<u>25.3</u>	9.3	6.0	31.5	30.0					
				U:	sing SB.	ERT Re	trieve	r												
-	-	14.9	15.6	15.1	20.4	16.6	22.7	8.2	11.0	15.3	26.4	7.0	5.3	20.0	10.8					
Claude-3-opus*	-	16.4	18.0	18.6	24.8	18.6	24.9	11.4	12.9	14.7	23.0	5.8	3.1	20.1	19.0					
GPT4*	-	17.7	18.2	18.5	26.3	17.5	27.2	8.8	11.8	17.5	24.3	10.3	5.0	22.3	23.5					
DeepSeek-R1	671B	<u>18.9</u>	<u>19.9</u>	20.8	31.0	20.2	26.0	10.3	12.4	<u>18.6</u>	22.6	4.5	8.4	<u>27.9</u>	<u>23.8</u>					
TongSearch-QR [†]	7B	18.5	18.7	20.5	25.5	18.4	25.5	11.2	11.6	18.4	23.4	9.5	4.7	25.2	28.0					
ReDI(ours)	8B	22.8	23.7	25.0	32.3	20.8	28.0	13.8	20.2	25.6	<u>25.2</u>	17.1	<u>6.2</u>	33.2	25.8					

and interpretation lead to more targeted retrieval across StackExchange domains. This may be that long-form expansions often introduce redundant reasoning or topic drift. Among baselines, feedback-based methods such as *ThinkQE* and *DIVER-QExpand* reach competitive results by iteratively refining queries. Notably, ReDI surpasses both despite not using any retrieval feedback, highlighting the crucial role of explicit decomposition for intent understanding. Nevertheless, ReDI struggles slightly on *Pony* and *AoPS*, where feedback-based methods excel. This highlights the opportunity for future work to explore the synergy of our decomposition with iterative refinement.

• Dense retrieval. With the SBERT retriever, which employs a 768-dimensional bi-encoder, single-query expansions yield limited improvements compared with the sparse setting. This may be due to the relatively shallow nature of the dense embedding space, which limits its ability to capture nuanced reasoning semantics. Despite this, ReDI achieves the best average nDCG@10 of 22.8%, with substantial gains on tasks such as Biology and StackOverflow. These findings indicate that structured decomposition and contextual interpretation can effectively compensate for the representational limits of lightweight dense retrievers. For more advanced dense encoders (e.g., ReasonIR-8B), Section 6.3 provides a detailed analysis of transferability and model interaction effects.

Overall, ReDI achieves superior performance across both sparse and dense retrieval settings with two lightweight retrievers. These results confirm the effectiveness of decomposition and interpretation for complex query understanding, particularly in domains that require abstract reasoning. In terms of efficiency, ReDI also offers a strong trade-off: as shown in Table 8 (Section A.1), its QU




Figure 3: nDCG@10 on BRIGHT with Qwen3 across different model sizes and reasoning modes.

stage (decompose + interpret) is slower than generating single longform expansions with models of the same size, but substantially faster than using larger models like DeepSeek-R1, while achieving comparable or even better retrieval performance.

6 Detailed Analysis

To better understand the effectiveness of our ReDI model, we conduct a comprehensive analysis to dissect the contributions of its core components and design choices. Our analysis consists of three parts: (i) **component analysis**: evaluate the individual contributions of reasoning, decomposition, and interpretation to ReDI; (ii) **strategy optimization**: examine the impact of different training paradigms and retrieval configurations on performance and practical utility. and (iii) **transferability evaluation**: assess ReDI's generalization ability on long documents, out-of-domain retrieval, and reasoning-based retrievers. The full results are provided in Appendix A.




Figure 4: nDCG@10 on BRIGHT with different nums of subquery + interpretation unit.

6.1 Component analysis

We begin by analyzing how each component – reasoning, decomposition, and interpretation – contributes to performance gains and whether their combination yields additive benefits. We also profile the runtime of each stage to quantify computational cost.

Contribution of the reasoning. We compare Qwen3 models of varying sizes (0.6B/4B/8B) in both without-thinking (direct answer) and with-thinking (reasoning-augmented) modes to assess how the model's intrinsic reasoning capacity affects downstream processing. As shown in Figure 3, both increased model size and explicit reasoning traces lead to consistent gains in retrieval performance on BRIGHT. It is noteworthy that the advantage of incorporating reasoning scales with the base model's size, suggesting that a more powerful base model maximizes the utility of decomposition and interpretation. These results underscore that effective retrieval for complex queries hinges on models that can reason before retrieving.

Contribution of interpretation on decomposition. We compare three strategies: (a) single long-form expansion ("Expansion"), (b) sub-query decomposition only ("Decomp."), and (c) decomposition with interpretation ("Decomp.+Interp."), to assess the added value of enriching each sub-query with contextual interpretation. As shown in Table 2, across both retrieval paradigms and generation models, the decomposition plus interpretation approach achieves the highest nDCG@10 on nearly all tasks and in overall averages. The results highlight that decomposition alone is insufficient – adding interpretation significantly improves retrieval by providing semantic grounding, reducing lexical mismatch, and enabling more complete coverage of complex, multifaceted queries.

Flexible vs. fixed decomposition. We compare fixed and flexible decomposition performance. As shown in Figure 4, ReDI with flexible decomposition consistently outperforms all fixed settings under different retrieval models. These results highlight the benefit of tailoring decomposition granularity to query complexity, allowing more retrieval units for complex queries and fewer for simpler ones, which improves overall retrieval performance. Although ReDI offers a flexible way to determine the number of decompositions dynamically, it is worth investigating more targeted methods for optimizing the decomposition for each specific query in the future.




Figure 5: Performance of sparse retriever under different k_3 and dense retriever at varying interpretation weights.

6.2 Strategy optimization

Beyond module design, we explore how different training and retrieval strategies influence ReDl's effectiveness.

Hyperparameter sensitivity. We analyze how retrieval performance responds to key hyperparameters in both sparse and dense settings. For sparse retrieval (Figure 5a), we vary the k_3 parameter, which controls query-side term frequency scaling. On shorter documents (the blue curve), smaller k_3 values (0.2–0.8) yield better results, peaking at $k_3 = 0.4$ with an nDCG@10 of 38.25. In contrast, for longer documents (the orange curve), Recall@1 improves with larger k_3 , reaching its maximum (25.98) at $k_3 = 5$ and plateauing thereafter. This suggests that shorter documents benefit from lower k_3 , which emphasizes matching a wider variety of query terms, while longer documents require higher k_3 to strengthen core term signals within more expansive content. Beyond $k_3 = 5$, further increases yield diminishing returns. For dense retrieval (Figure 5b), we vary the interpolation weight between the sub-query and its interpretation. nDCG@10 peaks at $\lambda = 0.5$ (23.67), while Recall@1 reaches its maximum at $\lambda = 0.4$ (23.12). Performance consistently drops as the interpolation shifts toward either extreme, highlighting the importance of balancing intent (sub-query) and contextual cues (interpretation). Further study of the complementarity between their embedding spaces would be an interesting future direction.

Fine-tuning method. We compare joint fine-tuning with two-stage fine-tuning (as detailed in Section 4.2) to study the impact of the learning strategy. As shown in Table 3, the two-stage training consistently outperforms joint training across both retrieval settings. Specifically, for sparse retrieval, it yields improvements of 8.2% in nDCG@10 on StackExchange tasks and 8.8% on overall tasks, while for dense retrieval, the gains reach 8.7% and 9.6%, respectively. These results demonstrate the advantage of decoupling learning objectives, which enable each stage to specialize without gradient interference, resulting in improved stability and overall retrieval effectiveness.

6.3 Transferability evaluation

Long documents retrieval. Table 4 reports the performance on the BRIGHT StackExchange long-document subset. In general, ReDI surpasses all reasoning-expanded baselines over the average Recall@1 for both sparse and dense retrieval. It achieves 26.0% in the sparse setting, leading all seven tasks, and 23.1% in the dense setting, ranking first on 4 of 7 tasks. These results highlight ReDI's strong

Table 2: Comparison of expansion, decomposition, and decomposition with interpretation on BRIGHT(nDCG@10).

QU Model	Method	Avg.All	Avg SF		StackExchange							ding	Th	eorem-b	ased
QC Model	Wictiou	71Vg.7111	TVg.5L	Bio.	Earth.	Econ.	Psy.	Rob.	Stack.	Sus.	Leet.	Pony	AoPS	TheoQ.	TheoT.
	Using BM25 Retriever														
	Expansion	22.6	28.8	47.0	47.7	19.1	30.4	15.0	22.3	20.0	18.6	7.7	3.7	23.1	16.2
ReDI	Decomp.	20.7	25.2	26.9	35.4	20.2	26.8	19.2	27.6	20.0	20.8	3.7	3.9	22.7	21.5
	Decomp.+Interp.	30.8	38.3	49.0	53.5	28.7	43.4	27.5	36.3	29.4	25.3	9.3	6.0	31.5	30.0
	Expansion	29.2	37.0	57.2	58.1	24.0	38.1	22.1	29.6	29.6	22.2	12.4	6.8	26.3	23.4
DeepSeek-R1	Decomp.	21.3	26.1	33.9	35.6	22.7	30.6	17.2	23.9	19.0	15.6	5.8	3.8	25.0	22.8
_	Decomp.+Interp.	31.9	39.9	56.6	56.4	31.7	41.8	26.3	36.8	29.4	21.2	13.5	6.3	30.6	32.0
				Usir	ig SBERT	T Retri	iever								
	Expansion	18.4	19.2	20.0	28.4	18.4	26.2	11.2	14.2	16.0	24.4	6.6	4.7	25.5	25.2
ReDI	Decomp.	20.2	20.1	22.4	25.1	17.4	24.3	11.6	17.8	22.2	24.4	17.9	3.5	31.8	23.9
	Decomp.+Interp.	22.8	23.7	25.0	32.3	20.8	28.0	13.8	20.2	25.6	25.2	17.1	6.2	33.2	25.8
	Expansion	18.9	19.9	20.8	31.0	20.2	26.0	10.3	12.4	18.6	22.6	4.5	8.4	27.9	23.8
DeepSeek-R1	Decomp.	21.0	20.9	22.3	30.3	20.5	25.3	11.0	16.8	20.2	20.9	22.0	5.9	30.7	25.6
	Decomp.+Interp.	22.1	22.7	25.1	31.0	21.9	26.6	12.3	18.7	23.0	18.9	18.2	4.4	35.2	29.2

Table 3: nDCG@10 on BRIGHT: Joint vs. two-stage training

Retriever	Model	StackExchange	Coding	Theo.	Avg.All
BM25	Joint	35.4	15.3	20.6	28.3
	Two-Stage	38.3	17.3	22.5	30.8
SBERT	Joint	21.8	19.4	19.1	20.8
	Two-Stage	23.7	21.2	21.7	22.8

Table 4: Recall@1 on the BRIGHT StackExchange long-document subset. *Results from SU et al. [32].

Model			S	tackEx	change	е						
Widuci	Bio.	Earth.	Econ.	Psy.	Rob.	Stack.	Sus.	Avg.				
		Using BM25 Retriever										
-	10.7	15.4	10.7	8.4	7.4	22.2	10.7	12.2				
Claude-3-opus*	26.8	13.5	13.4	28.2	7.9	28.2	11.8	18.5				
GPT4*	26.8	15.8	10.2	30.7	5.9	26.5	9.7	17.9				
DeepSeek-R1	26.8	20.0	14.4	30.2	14.9	33.3	10.6	21.5				
ReDI	28.4	22.4	21.2	32.0	19.8	36.3	21.7	26.0				
		Using	SBERT .	Retriev	er							
-	25.6	34.1	18.9	15.8	10.9	15.0	18.0	19.7				
Claude-3-opus*	34.8	31.6	21.8	15.8	8.9	15.8	16.6	20.8				
GPT4*	37.7	35.3	19.9	18.3	12.4	11.5	22.6	22.5				
DeepSeek-R1	35.6	34.8	16.0	15.3	8.9	15.0	19.9	20.8				
ReDI	36.2	32.8	22.8	20.8	10.9	16.2	22.2	23.1				

generalization to long documents and validate the effectiveness of our reasoning decomposition with interpretation strategy.

Out-of-domain retrieval. Finally, we examine the generalization ability of ReDI by evaluating it on shorter queries from the BEIR benchmark. As is shown in Table 5, ReDI with BM25 achieves an average nDCG@10 of 44.9 across nine tasks, surpassing Rank1-7B (40.9), MonoT5-3B (44.7), and RankLLaMA-7B (44.4). ReDI ranks among the top systems on multiple tasks, demonstrating strong out-of-domain generalization and confirming the effectiveness of our structured decomposition and interpretation model for real-world retrieval beyond BRIGHT.

Table 5: nDCG@10 on BEIR. *Results from Weller et al. [38]

Model	ΔεσυΔ	ClimE	DRP	FiO4	NEC	SciD	SciF	Touche.	TrecC	Δνσ
Wiodei	mgum.	ciiiii.	DDI.	11021.	IVI C.	ocio.	JCII.	Touciic.	TICCC.	rivg.
BM25 Flat	39.7	16.5	31.8	23.6	32.2	14.9	67.9	44.2	59.5	36.7
BM25S*	47.2	18.6	32.0	25.4	34.3	16.5	69.1	34.7	68.8	38.5
+ReDI	44.7	29.5	42.0	26.3	39.4	18.0	74.5	49.3	80.7	44.9
MonoT5-3B*	42.5	25.4	44.5	46.5	37.8	19.3	76.1	30.7	79.6	44.7
RankLLaMA-7B*	54.4	23.2	43.7	42.1	27.0	16.6	71.1	41.4	80.2	44.4
Rank1-7B*	42.8	15.0	38.9	39.5	36.2	17.2	77.2	22.8	81.9	40.9

Reasoning-based Retriever of ReasonIR-8B. Table 6 shows that with ReasonIR-8B⁶ as the retriever, ReDI performs less effectively than other single long-form expansion methods, with average scores of 29.1 across all tasks and 30.1 on StackExchange tasks, both lower than baseline results. This may be because ReasonIR is finetuned on synthetic reasoning-intensive, long-form queries (ranging from 300 to 2,000 natural words [31]) with a larger embedding size (4096 dimensions), enabling it to better capture the multidimensional intents in complex queries. A thorough investigation of this aspect is left for future work. Meanwhile, as shown in Table 1, BM25+ReDI achieves an average score of 38.3 on StackExchange tasks, outperforming the best baseline, ReasonIR+DIVER-QExpand (average score is 36.4). This further validates that ReDI can effectively boost the performance of lightweight retrievers, making it practical for real-world deployment. Beyond retrieval effectiveness, ReDI also demonstrates superior efficiency against single long-form QU, as it operates seamlessly with lightweight retrievers. As shown in Table 8 (Section A.1), BM25+ReDI and SBERT+ReDI are 58× and 4× faster than ReasonIR+Qwen3-8B during retrieval, achieving 1.6× higher overall efficiency. These results highlight ReDI's strong advantages in computational efficiency and scalability.

7 Conclusion

We propose **ReDI**, a reasoning-enhanced model for complex query understanding (QU) that addresses the core challenge of faithfully aligning a user's multi-faceted information need with retrievable evidence. By explicitly decomposing each complex query into targeted sub-queries and augmenting them with concise, intent-preserving

⁶https://huggingface.co/reasonir/ReasonIR-8B

Table 6: nDCG@10 on BRIGHT with ReasonIR-8B retriever.

Model	StackExchange	Coding	Theo.	Avg.All
GPT-4 Reason-query	31.4	25.6	25.4	29.9
TongSearch-QR	33.2	24.7	28.7	31.8
ThinkQE	34.2	28.0	28.9	30.8
DIVER-QExpand	36.4	22.6	29.4	32.6
ReDI	30.1	28.5	27.1	29.1

interpretations, our modular pipeline enables unit-level retrieval followed by principled score fusion. Experiments on the BRIGHT and BEIR benchmarks confirm that this design substantially improves retrieval effectiveness across both sparse and dense paradigms.

While ReDI is effective, several limitations highlight directions for future work. First, the improvements under dense retrieval are less pronounced than those under sparse retrieval, suggesting a potential mismatch between dense representations and fine-grained query semantics. Second, the current decomposition heavily relies on the LLM's internal knowledge, developing more controlled methods to decide what and when to decompose remains an intriguing avenue for exploration. Third, free-form interpretations may introduce spurious semantics that degrade retrieval accuracy, motivating future work on controllable generation, factuality constraints, and retrieval-grounded verification. Finally, while ReDI is competitive, ReasonIR's results suggest that its gains are less stable across domains, motivating future work on retriever-adaptive interpretations to further enhance robustness. Addressing these limitations would enhance both the generality and robustness of reasoning-based query understanding, paving the way for broader adoption in real-world tasks such as complex open-domain QA, conversational agents, and personalized search.

Acknowledgments

References

- Rakesh Agrawal, Sreenivas Gollapudi, Alan Halverson, and Samuel Ieong. 2009.
 Diversifying search results. In Proceedings of the Second ACM International Conference on Web Search and Data Mining (Barcelona, Spain) (WSDM '09).
 Association for Computing Machinery, New York, NY, USA, 5–14. https: //doi.org/10.1145/1498759.1498766
- [2] Mohannad Almasri, Catherine Berrut, and Jean-Pierre Chevallet. 2013. Wikipedia-based Semantic Query Enrichment. In Proceedings of the Sixth International Workshop on Exploiting Semantic Annotations in Information Retrieval (San Francisco, California, USA) (ESAIR '13). Association for Computing Machinery, New York, NY, USA, 5–8. https://doi.org/10.1145/2513204.2513209
- [3] Claudio Carpineto, Renato de Mori, Giovanni Romano, and Brigitte Bigi. 2001. An Information-theoretic Approach to Automatic Query Expansion. ACM Trans. Inf. Syst. 19, 1 (Jan. 2001), 1–27. https://doi.org/10.1145/366836.366860
- [4] Claudio Carpineto and Giovanni Romano. 2012. A Survey of Automatic Query Expansion in Information Retrieval. ACM Comput. Surv. 44, 1, Article 1 (Jan. 2012), 50 pages. https://doi.org/10.1145/2071389.2071390
- [5] Chi-Min Chan, Chunpu Xu, Ruibin Yuan, Hongyin Luo, Wei Xue, Yike Guo, and Jie Fu. 2024. RQ-RAG: Learning to Refine Queries for Retrieval Augmented Generation. arXiv preprint arXiv:2404.00610 (2024).
- [6] Yi Chang and Hongbo Deng. 2020. Query Understanding for Search Engines. https://doi.org/10.1007/978-3-030-58334-7
- [7] Stéphane Clinchant and Florent Perronnin. 2013. Aggregating Continuous Word Embeddings for Information Retrieval. In Proceedings of the Workshop on Continuous Vector Space Models and their Compositionality, Alexandre Allauzen, Hugo Larochelle, Christopher Manning, and Richard Socher (Eds.). Association for Computational Linguistics, Sofia, Bulgaria, 100–109. https://aclanthology.org/W13-2013/
- [8] Kevyn Collins-Thompson. 2009. Reducing the risk of query expansion via robust constrained optimization. In Proceedings of the 18th ACM Conference on Information and Knowledge Management (Hong Kong, China) (CIKM '09). Association for Computing Machinery, New York, NY, USA, 837–846. https://doi.org/10.1145/1645953.1646059
- //doi.org/10.1145/1645953.1646059
 [9] Hang Cui, Ji-Rong Wen, Jian-Yun Nie, and Wei-Ying Ma. 2003. Query Expansion by Mining User Logs. *IEEE Trans. on Knowl. and Data Eng.* 15, 4 (July 2003),

- 829-839. https://doi.org/10.1109/TKDE.2003.1209002
- [10] Van Dang and Bruce W. Croft. 2010. Query Reformulation using Anchor Text. In Proceedings of the Third ACM International Conference on Web Search and Data Mining (New York, New York, USA) (WSDM '10). Association for Computing Machinery, New York, NY, USA, 41–50. https://doi.org/10.1145/1718487.1718493
- [11] Valentina Franzoni and Alfredo Milani. 2012. PMING Distance: A Collaborative Semantic Proximity Measure. In Proceedings of the The 2012 IEEE/WIC/ACM International Joint Conferences on Web Intelligence and Intelligent Agent Technology - Volume 02 (WI-IAT '12). IEEE Computer Society, USA, 442–449. https://doi.org/ 10.1109/WI-IAT.2012.226
- [12] Evgeniy Gabrilovich and Shaul Markovitch. 2007. Computing semantic relatedness using Wikipedia-based explicit semantic analysis. In Proceedings of the 20th International Joint Conference on Artifical Intelligence (Hyderabad, India) (IJ-CAI'07). Morgan Kaufmann Publishers Inc., San Francisco, CA, USA, 1606–1611.
- [13] Luyu Gao, Xueguang Ma, Jimmy J. Lin, and Jamie Callan. 2022. Precise Zero-Shot Dense Retrieval without Relevance Labels. ArXiv abs/2212.10496 (2022). https://api.semanticscholar.org/CorpusID:254877046
- [14] Yijun Ge, Sahel Sharifymoghaddam, and Jimmy Lin. 2025. Lighting the Way for BRIGHT: Reproducible Baselines with Anserini, Pyserini, and RankLLM. arXiv:2509.02558 [cs.IR] https://arxiv.org/abs/2509.02558
- [15] Gemini. 2025. Deep Research. https://gemini.google/overview/deep-research/ Gemini blog post.
- [16] Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. arXiv preprint arXiv:2501.12948 (2025).
- [17] Jinhao Jiang, Jiayi Chen, Junyi Li, Ruiyang Ren, Shijie Wang, Wayne Xin Zhao, Yang Song, and Tao Zhang. 2024. Rag-star: Enhancing deliberative reasoning with retrieval augmented verification and refinement. arXiv preprint arXiv:2412.12881 (2024).
- [18] Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense Passage Retrieval for Open-Domain Question Answering. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), Bonnie Webber, Trevor Cohn, Yulan He, and Yang Liu (Eds.). Association for Computational Linguistics, Online, 6769–6781. https://doi.org/10.18653/v1/2020.emnlp-main.550
- [19] Reiner Kraft and Jason Zien. 2004. Mining Anchor Text for Query Refinement. In Proceedings of the 13th International Conference on World Wide Web (New York, NY, USA) (WWW '04). Association for Computing Machinery, New York, NY, USA, 666–674. https://doi.org/10.1145/988672.988763
- [20] Victor Lavrenko and W. Bruce Croft. 2001. Relevance based language models. In Proceedings of the 24th Annual International ACM SIGIR Conference on Research and Development in Information Retrieval (New Orleans, Louisiana, USA) (SIGIR '01). Association for Computing Machinery, New York, NY, USA, 120–127. https: //doi.org/10.1145/383952.383972
- [21] Yibin Lei, Tao Shen, and Andrew Yates. 2025. ThinkQE: Query Expansion via an Evolving Thinking Process. ArXiv abs/2506.09260 (2025). https://api. semanticscholar.org/CorpusID:279306340
- [22] Jimmy Lin and W. John Wilbur. 2007. PubMed related articles: a probabilistic topic-based model for content similarity. BMC Bioinformatics 8, 1 (2007), 423. https://doi.org/10.1186/1471-2105-8-423
- [23] Wenhan Liu, Xinyu Ma, Weiwei Sun, Yutao Zhu, Yuchen Li, Dawei Yin, and Zhicheng Dou. 2025. ReasonRank: Empowering Passage Ranking with Strong Reasoning Ability. arXiv preprint arXiv:2508.07050 (2025).
- [24] Mei Long, Duolin Sun, Dan Yang, Junjie Wang, Yue Shen, Jian Wang, Peng Wei, Jinjie Gu, and Jiahai Wang. 2025. DIVER: A Multi-Stage Approach for Reasoning-intensive Information Retrieval. https://api.semanticscholar.org/CorpusID:280567061
- [25] Yuanhua Lv, ChengXiang Zhai, and Wan Chen. 2011. A Boosting Approach to Improving Pseudo-relevance Feedback. In Proceedings of the 34th International ACM SIGIR Conference on Research and Development in Information Retrieval (Beijing, China) (SIGIR '11). Association for Computing Machinery, New York, NY, USA, 165-174. https://doi.org/10.1145/2009916.2009942
- [26] Xinbei Ma, Yeyun Gong, Pengcheng He, Hai Zhao, and Nan Duan. 2023. Query Rewriting for Retrieval-Augmented Large Language Models. ArXiv abs/2305.14283 (2023). https://api.semanticscholar.org/CorpusID:258841283
- [27] OpenAI. 2025. Introducing Deep Research. https://openai.com/index/introducing-deep-research/ OpenAI blog post.
- [28] Xubo Qin, Jun Bai, Jiaqi Li, Zixia Jia, and Zilong Zheng. 2025. TongSearch-QR: Reinforced Query Reasoning for Retrieval. ArXiv abs/2506.11603 (2025). https://api.semanticscholar.org/CorpusID:279391821
- [29] Stephen E. Robertson. 1991. On Term Selection for Query Expansion. J. Doc. 46, 4 (Jan. 1991), 359–364. https://doi.org/10.1108/eb026866
- [30] Joseph John Rocchio. 1971. Relevance Feedback in Information Retrieval. https://api.semanticscholar.org/CorpusID:61859400
- [31] Rulin Shao, Rui Qiao, Varsha Kishore, Niklas Muennighoff, Xi Victoria Lin, Daniela Rus, Bryan Kian Hsiang Low, Sewon Min, Wen tau Yih, Pang Wei Koh,

and Luke S. Zettlemoyer. 2025. ReasonIR: Training Retrievers for Reasoning Tasks. *ArXiv* abs/2504.20595 (2025). https://api.semanticscholar.org/CorpusID: 278171297

- [32] Hongjin SU, Howard Yen, Mengzhou Xia, Weijia Shi, Niklas Muennighoff, Han yu Wang, Liu Haisu, Quan Shi, Zachary S Siegel, Michael Tang, Ruoxi Sun, Jinsung Yoon, Sercan O Arik, Danqi Chen, and Tao Yu. 2025. BRIGHT: A Realistic and Challenging Benchmark for Reasoning-Intensive Retrieval. In The Thirteenth International Conference on Learning Representations. https://openreview.net/forum?id=ykuc5q381b
- [33] Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. 2021. BEIR: A Heterogenous Benchmark for Zero-shot Evaluation of Information Retrieval Models. ArXiv abs/2104.08663 (2021). https://api. semanticscholar.org/CorpusID:233296016
- [34] Ellen M. Voorhees. 1994. Query Expansion using Lexical-semantic Relations. In Proceedings of the 17th Annual International ACM SIGIR Conference on Research and Development in Information Retrieval (Dublin, Ireland) (SIGIR '94). Springer-Verlag, Berlin, Heidelberg, 61–69.
- [35] Jianyou Wang, Kaicheng Wang, Xiaoyue Wang, Prudhviraj Naidu, Leon Bergen, and Ramamohan Paturi. 2023. DORIS-MAE: Scientific Document Retrieval using Multi-level Aspect-based Queries. In Proceedings of the 37th International Conference on Neural Information Processing Systems (New Orleans, LA, USA) (NIPS '23). Curran Associates Inc., Red Hook, NY, USA, Article 1668, 16 pages.
- [36] Liang Wang, Nan Yang, and Furu Wei. 2023. Query2doc: Query Expansion with Large Language Models. In Conference on Empirical Methods in Natural Language Processing. https://api.semanticscholar.org/CorpusID:257505063
- [37] Xuanhui Wang and ChengXiang Zhai. 2008. Mining term association patterns from search logs for effective query reformulation. In *International Conference* on *Information and Knowledge Management*. https://api.semanticscholar.org/ CorpusID:12406071
- [38] Orion Weller, Kathryn Ricci, Eugene Yang, Andrew Yates, Dawn Lawrie, and Benjamin Van Durme. 2025. Rankl: Test-time compute for reranking in information retrieval. arXiv preprint arXiv:2502.18418 (2025).
- [39] Tomer Wolfson, Mor Geva, Ankit Gupta, Matt Gardner, Yoav Goldberg, Daniel Deutch, and Jonathan Berant. 2020. Break It Down: A Question Understanding Benchmark. Transactions of the Association for Computational Linguistics 8 (2020), 183–198. https://doi.org/10.1162/tacl_a_00309
- [40] Oliver Young, Yixing Fan, Ruqing Zhang, Jiafeng Guo, Maarten de Rijke, and Xueqi Cheng. 2024. GaQR: An Efficient Generation-augmented Question Rewriter. In Proceedings of the 33rd ACM International Conference on Information and Knowledge Management (Boise, ID, USA) (CIKM '24). Association for Computing Machinery, New York, NY, USA, 4228–4232. https://doi.org/10.1145/3627673.
- [41] Huaixiu Steven Zheng, Swaroop Mishra, Xinyun Chen, Heng-Tze Cheng, Ed H. Chi, Quoc V Le, and Denny Zhou. 2024. Take a Step Back: Evoking Reasoning via Abstraction in Large Language Models. In The Twelfth International Conference on Learning Representations. https://openreview.net/forum?id=3bq3jsvcQ1

A Appendix

A.1 Supplementary Experiments

Illustration of General search and AI search. As shown in Figure 6, the search framework provides a comparative illustration of traditional general search and AI-powered search in response to a technical query about partitioning household food expenditures into producing industries. The left displays conventional search engine results, which return relevant articles and sources but require the user to extract and synthesize information independently. In contrast, the right demonstrates an AI search, where the AI assistant directly generates a synthesized, context-specific answer by referencing authoritative data sources such as the U.S. Bureau of Economic Analysis (BEA) Input-Output tables. This side-by-side comparison highlights the enhanced efficiency and specificity of AI-driven search tools for complex, information-intensive queries.



Figure 6: General search vs. AI search illustration.

Fusion Methods. We compare four strategies for aggregating retrieval results across units: score summation (sum), highest score (max), reciprocal rank fusion (RRF), and single merged query (concat). As shown in Figure 7, sum fusion consistently delivers the best performance. While concat performs comparably to sum in sparse retrieval, its performance drops sharply in dense retrieval, indicating that long merged queries dilute semantic focus and confuse dense encoders. RRF and max yield moderate or lower results across all settings. These results highlight the robustness of score-based aggregation, particularly in dense retrieval, where preserving unit granularity is crucial for maintaining semantic precision.




Figure 7: nDCG@10 on BRIGHT with different retrieval fusion methods.

Coin Dataset Validation. To verify that the selected Coin queries indeed necessitate decomposition, we conducted a comparative answering experiment on *retained* (complex) versus *excluded* (simple) queries. For each query, we retrieve the top-4 documents via a standard search API and prompt DeepSeek-R1 to generate an answer by synthesizing information from those documents. We then evaluated each answer along four key dimensions of quality: Accuracy(Acc.) (correctness of the information), Completeness(Compl.) (coverage of all aspects of the query), Coherence(Coh.) (logical consistency and fluency), and Conciseness(Conc.) (absence of unnecessary or off-topic content). Each dimension was rated on a 1–5 scale by DeepSeek-R1 judger, and we averaged these ratings to obtain an overall QA score for the query.

As shown in Table 7, excluded queries achieved high QA scores (3.65/5), indicating that a single round of retrieval and LLM answering often sufficed for these queries. In contrast, our Coin dataset retained queries scored much lower on average (1.95/5), with particularly poor performance on completeness (1.9/5). This result confirms that Coin's queries inherently demand multi-faceted reasoning and are ill-served by straightforward retrieval, underscoring the importance of an intent-decomposition approach.

Table 7: DeepSeek-R1 average ratings (excluded vs. retained).

Type	Acc.	Compl	. Coh.	Conc	. Avg
Excluded queries	3.8	3.6	3.7	3.5	3.65
Retained queries	2.1	1.9	2.0	1.8	1.95

Efficiency Analysis. We evaluate the computational efficiency of each stage on an A100 GPU, as summarized in Table 8. For ReDI, the QU (decomposition and interpretation) takes 8.50s per query in the sparse setting and 7.74s in the dense setting, while retrieval and fusion cost only 0.14s for BM25 and 2.15s for SBERT, leading to total runtimes of 8.64s and 9.89s, respectively. By comparison, using the reasoning-based retriever ReasonIR-8B, Qwen3-8B requires 5.34s for single long-form reasoning expansion and 8.16s for retrieval, totaling 13.50s per query, while DeepSeek-R1 increases the cost to 13.50s for expansion and 16.77s for retrieval, reaching an overall runtime of 30.27s. Although ReDI spends more time on query understanding, it significantly reduces retrieval overhead, resulting in higher overall efficiency and faster end-to-end processing while maintaining strong retrieval performance.

Table 8: Runtime of different configurations.

QU Model	Retriever	Setting	Avg./Q (s)	Total(s)
ReDI	BM25	Decomp. + Interp. Retrieve	8.50 0.14	8.64
ReDI	SBERT	Decomp. + Interp. Retrieve	7.74 2.15	9.89
Qwen3-8B	ReasonIR	Single long-form Retrieve	5.34 8.16	13.50
DeepSeek-R1	ReasonIR	Single long-form Retrieve	13.50 16.77	30.27

A.2 Complete Experimental Results

Role of Model Reasoning. Table 9 presents the complete experimental results in Figure 3. Across BM25, scaling the rewrite model and enabling "think" generally increase nDCG@10; Qwen3-8B(think) gives the largest gains among Qwen variants. Under

SBERT, gains from "think" are smaller and sometimes negative for small models, suggesting dense encoders are less tolerant of verbose/latent-logic rewrites. In both retrievers, **ReDI** surpasses all size/think settings, indicating that structured decomposition + interpretation contributes more than raw model size or implicit chain-of-thought.

Hyperparameter Sensitivity. Table 10 presents the complete experimental results in Figure 5a. BM25 attains its best average around $k_3 \approx 0.4$, with clear degradation as k_3 increases (i.e., approaching linear qtf). Small k_3 strengthens repeated key terms in short units (beneficial for decomposition), whereas large k_3 reduces this advantage and hurts long-document domains. The curve is smooth with a broad optimum $k_3 \in [0, 0.8]$, indicating stable tuning.

Table 11 presents the complete experimental results in Figure 5b. SBERT peaks near description weight $\lambda=0.5$, confirming that balancing the original sub-query and its interpretation yields the best alignment with document embeddings. Over-weighting interpretations $\lambda \geq 0.8$ or the sub-query $\lambda \leq 0.2$ both reduce effectiveness, especially on theory-heavy sets.

Fine-tuning Paradigm. Table 12 presents the complete experimental results in Table 3. Two-stage training outperforms joint training for both BM25 and SBERT, with the largest gains on Stack-Exchange and Theorem-based. Decoupling decomposition/interpretation learning from retrieval scoring likely reduces optimization interference and improves stability.

Reasoning-based Retriever of ReasonIR-8B.. Table 13 presents the complete experimental results in Table 6. With ReasonIR-8B, systems built on single long-form rewrites lead on StackExchange and Theorem-based, while ReDI is competitive on Coding. This highlights a retriever-adaptive trade-off: specialized high-capacity dense encoders favor globally coherent rewrites; decomposition brings larger benefits with lexical or lighter dense retrievers and on modular tasks.

Table 9: nDCG@10 on BRIGHT with Qwen3 across different model sizes and reasoning models.

Param	Think Mode	Avg.All	Avg.SE			Stack	Exch	ange			Сос	ding	Th	eorem-b	ased
	111111111111111111111111111111111111111	11.8.121	11.8.02	Bio.	Earth.	Econ.	Psy.	Rob.	Stack.	Sus.	Leet.	Pony	AoPS	TheoQ.	TheoT.
Using BM25 Retriever															
-	-	14.5	17.2	18.9	27.2	14.9	12.5	13.6	18.4	15.0	24.4	7.9	6.2	10.4	4.9
0.6B	Disabled	15.3	19.7	22.0	31.9	17.0	23.9	13.9	16.6	12.7	14.4	3.4	1.1	15.5	11.3
0.6B	Enabled	15.7	19.3	26.7	26.2	15.3	21.6	13.5	14.6	17.0	20.6	6.3	2.3	15.8	8.0
4B	Disabled	19.0	24.9	28.8	39.3	10.8	27.3	19.6	21.0	16.7	19.4	3.7	2.4	19.3	19.5
4B	Enabled	20.1	25.7	32.6	40.5	18.4	28.3	17.3	22.5	20.3	18.8	3.8	3.0	17.6	18.0
8B	Disabled	20.7	26.3	32.8	43.3	18.2	30.3	19.6	22.4	17.3	19.4	3.7	2.4	19.3	19.5
8B	Enabled	22.8	29.0	40.1	46.0	20.9	29.6	21.5	25.0	20.2	16.9	6.4	3.1	22.5	21.7
					Using	SBERT	Retri	ever							
-	-	14.9	15.6	15.1	20.4	16.6	22.7	8.2	11.0	15.3	26.4	7.0	5.3	20.0	10.8
0.6B	Disabled	10.7	12.6	12.4	19.0	11.8	19.1	10.0	6.8	9.1	12.3	0.7	3.5	14.3	9.1
0.6B	Enabled	10.3	12.2	13.5	18.2	13.9	3.3	9.1	9.1	18.3	9.5	4.0	3.6	15.7	5.1
4B	Disabled	13.7	14.4	17.9	18.3	13.5	20.4	7.6	10.9	12.4	15.8	3.5	5.4	19.1	19.7
4B	Enabled	14.3	15.0	15.1	20.8	12.0	22.7	5.4	12.3	16.5	18.0	6.1	1.8	23.0	17.6
8B	Disabled	15.3	16.6	17.5	24.4	14.4	21.9	6.5	10.8	20.7	18.9	10.8	1.3	22.7	13.9
8B	Enabled	16.8	17.2	15.7	23.0	15.7	22.1	9.3	14.9	19.8	18.2	11.2	3.4	26.9	21.2

Table 10: Performance of sparse retriever (BM25) under different k_3 .

1												
Theorem-based												
Q. TheoT.												
06 29.16												
57 29.64												
47 30.02												
36 30.03												
55 29.90												
68 29.47												
06 28.43												
93 27.69												
03 27.56												
96 27.56												
96 27.26												
8. 9. 8.												

Table 11: Performance of dense retriever (SBERT) at varying interpretation weights.

intern	Avg. all	Avo SF		StackExchange								Theorem-based			
inter p.w	1116	1116.02	Bio.	Earth.	Econ.	Psy.	Rob.	Stack.	Sus.	Leet.	Pony	AoPS	TheoQ.	TheoT.	
0.9	19.79	21.42	22.34	30.86	18.19	25.81	10.05	18.35	24.33	18.86	13.17	3.79	29.02	22.71	
0.8	20.72	22.36	23.17	31.93	19.16	27.05	10.73	19.13	25.38	19.96	13.93	5.10	29.99	23.07	
0.7	21.53	22.73	24.17	32.70	19.04	27.46	11.29	19.64	24.81	22.56	14.77	6.40	31.25	24.24	
0.6	22.27	23.40	25.07	32.60	20.12	28.11	13.10	19.86	24.92	24.28	15.68	6.18	32.09	25.23	
0.5	22.76	23.67	24.97	32.30	20.77	28.00	13.79	20.24	25.59	25.22	17.11	6.19	33.22	25.79	
0.4	22.40	23.19	24.80	31.41	19.91	27.71	13.93	19.66	24.88	25.05	17.81	5.04	32.99	25.61	
0.3	22.04	22.76	24.13	30.70	19.65	27.03	13.48	19.86	24.48	25.25	17.70	4.72	32.66	24.80	
0.2	21.52	21.93	24.12	29.81	18.63	25.72	12.75	18.98	23.53	25.13	18.01	4.35	32.48	24.78	
0.1	20.99	21.31	24.00	28.71	17.84	24.45	12.50	18.57	23.07	24.35	18.20	4.11	31.66	24.41	

Table 12: nDCG@10 on BRIGHT: Joint vs. Two-Stage Training

Method	Avg. all	Avg. SE	StackExchange								Coding		Theorem-based			
			Bio.	Earth. I	Econ.	Psy.	Rob.	Stack.	Sus.	Leet.	Pony	AoPS	TheoQ.	TheoT.		
Using BM25 Retriever																
Joint	28.3	35.4	46.7	49.9	27.2	38.4	24.5	33.8	27.0	23.6	6.9	5.5	28.3	28.1		
Two-Stage	30.8	38.3	49.0	53.5	28.7	43.4	27.5	36.3	29.4	25.3	9.3	6.0	31.5	30.0		
Using SBERT Retriever																
Joint	20.8	21.8	22.7	29.9	18.9	25.7	12.0	18.9	24.8	24.0	14.8	5.1	30.2	22.1		
Two-Stage	22.8	23.7	25.0	32.3	20.8	28.0	13.8	20.2	25.6	25.2	17.1	6.2	33.2	25.8		

Table 13: nDCG@10 on BRIGHT Benchmark with ReasonIR-8B retriever. † Results from Long et al. [24].

OU Model	Params	Avg. all	Avg. SE	StackExchange							Coding		Theorem-based		
QC Model				Bio.	Earth.	Econ.	Psy.	Rob.	Stack. Sus.	Leet.	Pony	AoPS	TheoQ.	TheoT.	
GPT-4 Reason-query [†]	-	29.9	31.4	43.6	42.9	32.7	38.8	20.9	25.8 27.5	31.5	19.6	7.4	33.1	35.7	
${\rm XRR2}^{\dagger}$	-	30.8	32.6	47.1	46.2	29.6	39.9	22.3	32.8 24.6	24.7	27.7	7.0	33.6	32.9	
TongSearch-QR [†]	7B	31.8	33.2	46.2	45.1	31.1	39.0	22.4	28.4 31.2	26.4	22.9	10.3	38.0	37.7	
ThinkQE [†]	14B	30.8	34.2	44.9	45.2	31.9	40.9	24.6	33.5 28.9	32.5	23.5	8.5	41.1	37.1	
DIVER-QExpand [†]	14B	32.6	36.4	49.4	44.7	32.4	44.0	26.6	31.8 29.0	32.3	12.8	9.1	40.7	38.4	
ReDI	8B	29.1	30.1	31.8	38.9	26.5	34.4	21.3	32.2 25.5	35.7	21.3	7.6	39.0	34.7	